

# Specification Sheet

## OGAS - White Glossy, Opaque Polypropylene film

---

**Face:** White, glossy, opaque polypropylene film, biaxially stretched, with special surface treatment for better printability.

**Applications and use:** Perfect for any application demanding removability of the label. Suitable for cosmetic products, cleaning agents etc., as well as for applications demanding resistance to chemicals or weather.

<b>Thickness</b>	60µm
<b>Basic Weight</b>	45g/m <sup>2</sup>

---

**Adhesive:** Permanent, transparent acrylic based adhesive.

**Applications and use:** It has a good resistance to light, heat and ageing and is insensitive to humidity, soap and oil. Also universally applicable on various surfaces.

<b>Initial Tack</b>	High
<b>Peel Adhesion</b>	High
<b>Min. App. Temp</b>	0°C
<b>Temp Range</b>	-30°C to +80°C
<b>UV Resistance</b>	Good

---

**Liner:** White, supercalendered glassine.

**Applications and use:** Ideal for labelling machines equipped with optical or mechanical scanners.

<b>Thickness</b>	56µm
<b>Basic Weight</b>	64g/m <sup>2</sup>

---

### Shelf Life:

2 years when stored at 20+5°C a relative humidity of 45+5%.

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the company's conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate user's responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.