

Specification Sheet

PEEL

Face:

White label paper, semi-gloss coated on one side

Basic Weight	approx. 80 g/m ²
---------------------	-----------------------------

Adhesive:

Removable, acrylic based adhesive.

Initial Tack	Medium
Peel Adhesion	Low (removable)
Shear	High
Min. App. Temp	-25 °C
Temp Range	-40 °C to +60 °C (up to 200 °C for short periods - hot fusing)

Liner:

Honey glassine liner

Basic Weight	65 gsm ±5%
---------------------	------------

Application:

Suitable for applications requiring medium tack combined with good removability. It is particularly suited for labelling surfaces like cardboard, PE-Films and steel. Removability may be impaired if applied on certain surface coated materials. Features excellent resistance to light, heat and ageing.

Shelf Life:

Storing at a temperature of 20 ± 5 °C, a relative humidity of 45 ± 5 % and a dark storage is recommended. Moisture, heat and direct sunlight have to be avoided. The shelf life up to 1 year from date of production.

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the company's conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate user's responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.