

Specification Sheet

PADA Semi-Gloss Opaque Adhesive Permanent

Face:

A white, semi-gloss wood free printing paper, back printed with opaque dense blue prior to adhesive coating. This is a high opacity product designed to obliterate and possibly correct unwanted or redundant text.

| | |
|------------------|---------------------|
| Thickness | 95 micron $\pm 5\%$ |
| Thickness | 95 gsm $\pm 5\%$ |

Adhesive:

A permanent pressure sensitive modified acrylic aqueous dispersion.

| | |
|-----------------------|----------------|
| Initial Tack | High |
| Peel Adhesion | High |
| Min. App. Temp | 0°C |
| Temp Range | -20°C to +80°C |
| UV Resistance | Good |

Liner:

White, supercalendered glassine

| | |
|---------------------|---------------------|
| Thickness | 55 micron $\pm 5\%$ |
| Basic Weight | 60 gsm $\pm 5\%$ |

Shelf Life:

2 years when stored at 22°C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the company's conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate user's responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.