

Specification Sheet

SPET Clear Gloss PET Overlam 23M μ Permanent

Face:

A high gloss, glass clear, polyester PET film. A flexible strong and durable film used for overlaminating pre-printed labels. The film has excellent resistance to moisture and most chemicals. It is not print-receptive.

Thickness	23 micron \pm 5%
Basic Weight	

Adhesive:

A permanent modified acrylic aqueous dispersion.

Initial Tack	Good
Final Adhesion	Very High
Min. App. Temp	+5°C
Temp Range	-20°C to +120°C
UV Resistance	Excellent

This overlaminate is the preferred choice of printers using hot foil and other intermittent action presses. Exhibiting high gloss and excellent clarity, this film enhances appearance and provides ultimate print protection. Although care should still be exercised with regard to tensions, this film resists stretching when compared to other films offered for the same purpose.

Liner:

A supercalendered siliconised white glassine paper, with high mechanical resistance to tearing.

Thickness	56 micron \pm 5%
Basic Weight	65 gsm \pm 5%

Shelf Life:

2 years when stored at 22°C / 50% RH.

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the company's conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate user's responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.