

Specification Sheet

SABA White High Density Matt White PE / Permanent Adhesive

Face:

A matt white high density polyethylene, top coated to be computer imprintable, print-receptive and thermal transfer printing. Polyethylene is generally the preferred film for proprietary labelling of flexible containers. This particular grade with a wide specification high performance adhesive may be used for labelling of flexible packs and containers stored in fridges and freezers. E.g. ice cream tubs.

Thickness	95 micron $\pm 5\%$
Basic Weight	75 gsm $\pm 5\%$

Complies with BfR XXXVI recommendations for direct contact with dry and/or greasy food.

Adhesive:

A permanent rubber based adhesive suitable for deep freeze use.

Initial Tack	High
Final Adhesion	Very High
Min. App. Temp	-0°C
Temp Range	-40°C to +80°C
UV Resistance	Excellent

This adhesive is BGVV certified safe for direct contact with dry and moist, non-fatty and non-alcoholic foodstuffs, it is FDA certified as being suitable for indirect contact with foodstuffs. It also meets the requirements for the "Toy Standard" EN 71-3

BS5609 Approved

Liner:

A supercalendered siliconised white glassine paper, with high mechanical resistance to tearing.

Thickness	68 micron $\pm 5\%$
Basic Weight	80 gsm $\pm 5\%$

Shelf Life:

2 years when stored at 22°C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the company's conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate user's responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.