

# Specification Sheet

## DEVI 50 $\mu$ Satin White Destructible PVC – Permanent Adhesive

---

### Face:

50 $\mu$  satin white destructible PVC with consistent satin level and excellent printability via conventional inks and thermal transfer when used in conjunction with resin and resin/wax. Designed as a security film for tamper evidence.

<b>Thickness</b>	50 $\mu$ $\pm$ 10%
<b>Basic Weight</b>	23gsm $\pm$ 10%

---

### Adhesive:

PATI is a high performance permanent acrylic adhesive that offers excellent chemical, humidity and elevated temperature resistance. PATI exhibits high elevated temperature shear resistance which results in low adhesive ooze. PATI offers excellent adhesion on a broad range of surfaces. Automotive approved.

<b>Dimensional Stability</b>	Excellent
<b>Chemical Resistance</b>	Good
<b>Min. App. Temp</b>	+40°F (+4°C)
<b>Temp Range</b>	-40°C to +85°C
<b>Outdoor Durability</b>	5 Years

Complies with FDA 175.105 and with BgVV XIV recommendations for direct contact with dry non-fatty foodstuff.

---

### Liner:

7K is a 82gsm white polycoated glassine release liner. The one side PE coated liner ensures adhesive smoothness. Suitable for high speed dispensing.

<b>Thickness</b>	74 $\mu$ $\pm$ 10%
<b>Basic Weight</b>	82 gsm

---

### Shelf Life:

2 years when stored at 22°C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the company's conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate user's responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.