

Specification Sheet

PBBB Coated White Woodfree Paper

Face:

White coated, calendared, woodfree paper.

Thickness	65 micron $\pm 10\%$
Basic Weight	80 gsm $\pm 10\%$

Adhesive:

General purpose permanent acrylic water based adhesive. Good adhesion to a wide variety of substrates, including non-polar surfaces. Good behaviour at low temperatures. The adhesive conforms with the Bfr XIV regulations for direct contact with dry and moist non-fatty foodstuffs (ISEGA certificate No. 27970 U 09).

Initial Tack	High
Final Adhesion	Very High
Min. App. Temp	+0°C
Temp Range	-30°C to + 80°C

Liner:

A supercalendered siliconised white glassine paper, with high mechanical resistance to tearing. Colour is white.

Thickness	59 micron $\pm 10\%$
Basic Weight	52 gsm $\pm 10\%$

Shelf Life:

4 years (from date of production) when stored at 20°C $\pm 5^\circ\text{C}$ and 45 $\pm 5\%$ RH.

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the company's conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate user's responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.