

# Specification Sheet

## SDAA Top Coated Gloss Clear PP 50 microns Perm

---

### Face:

Clear gloss, biaxially orientated, top coated polypropylène film. The film conforms to the European Directive 2002/95/EC (RoHS).

<b>Thickness</b>	50 micron
<b>Basic Weight</b>	

---

### Adhesive:

Permanent acrylic water based adhesive. Specially developed for synthetic face materials due to its excellent clarity Good adhesion to non-polar surfaces. The adhesive conforms with the regulations for direct contact with dry, moist and such kind of fatty foodstuffs which have a reduction factor of at least 3 according to the EC directive 85/572/CEE (ISEGA certificate No. 29957 U 10).

<b>Initial Tack</b>	Good
<b>Final Adhesion</b>	Very High
<b>Min. App. Temp</b>	+5°C
<b>Temp Range</b>	-10°C to +80°C
<b>UV Resistance</b>	Excellent

---

### Liner:

Supercalendered glassine paper, white.

<b>Thickness</b>	55 micron $\pm 5\%$
<b>Basic Weight</b>	62 gsm $\pm 5\%$

---

### Shelf Life:

2 years when stored at 22°C / 50% RH.

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the company's conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate user's responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.