

Specification Sheet

PAAA Gloss White Paper – Permanent Adhesive

Face:

A glossy white paper which offers an excellent quality of print with all traditional printing methods. PAAA is used for high-quality labels with pretentious printing, such as ornamental, advertising and product labels.

Thickness	71µm
Basic Weight	85g/m ²

The paper complies with BfR XXXVI recommendations for direct contact with dry and/or greasy food.

Adhesive:

Storing at a temperature of 20±5°C, a relative humidity of 45±5% and a dark storage is recommended. Moisture, heat and direct sunlight have to be avoided.

Initial Tack	High
Peel Adhesion	Very High
Min. App. Temp	0°C
Temp Range	-30°C to +80°C (up to 200°C for short periods – hot fusing)
UV Resistance	Excellent

All ingredients of adhesive comply with recommendations BfR XIV or FDA 21 CFR 175.105 (Adhesives).

Liner:

The supercalendered glassine is perfectly suited for assignment in labelling machines equipped with optical or mechanical scanners.

Colour	Honey
Thickness	52µm
Basic Weight	59g/m ²

Shelf Life:

4 years when stored at 22°C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the company's conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate user's responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.