

Specification Sheet

VAAA Gloss Yellow Vinyl Permanent

Face:

A monomeric gloss finished calendered polyvinyl chloride (PVC) soft handle plasticised film, exhibiting excellent mechanical resistance and flexibility. Cadmium free. The film conforms to the European Directive 2002/95/EC (RoHS).

Thickness	80 micron \pm 10%
Basic Weight	110 gsm \pm 10%

Adhesive:

A permanent modified acrylic aqueous dispersion.

Initial Tack	Medium
Final Adhesion	High
Min. App. Temp	-5°C
Temp Range	-40°C to +120°C
UV Resistance	Excellent

Complies with FDA 175.105 and with BgVV recommendations for indirect contact with foodstuff.

Liner:

A supercalendered siliconised white glassine paper, with high mechanical resistance to tearing.

Thickness	57 micron \pm 10%
Basic Weight	65 gsm \pm 10%

Shelf Life:

2 years when stored at 22°C / 50% RH.

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the company's conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate user's responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.