

Specification Sheet

ZBZZ Matt White Laser Polyester Permanent

Face:

A matt white polyester, top coated to be computer imprintable and thermal transfer print-receptive. Specially designed for hot fuse sheet fed laser printing where there is a requirement for variable information on a durable label for manufactured part labelling, tracking, stock control, racked storage identification etc.

Thickness	58 micron $\pm 5\%$
Printability	75 gsm $\pm 5\%$

Adhesive:

A permanent, acrylic aqueous, dispersion. Specially designed for labelling of HDPE drums and other rough substances.

Initial Tack	High
Final Adhesion	Very High
Min. App. Temp	0°C
Temp Range	-20°C to +70°C
UV Resistance	Poor

UV resistance of this adhesive is limited.

BS5609 Approved.

Liner:

A white one sided siliconised kraft paper, that has good layflat qualities and can be back-printed.

Thickness	88 micron $\pm 5\%$
Basic Weight	100 gsm $\pm 5\%$

Shelf Life:

2 years when stored at 22°C / 50% RH

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the company's conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate user's responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.