

Specification Sheet

VPAA (R) Gloss White Vinyl Permanent

Face:

Gloss white plasticised vinyl film, with good flexibility and conformability to curved surface.

Thickness	80 micron $\pm 10\%$
Basic Weight	110 gsm $\pm 10\%$

Adhesive:

A permanent adhesive with high adhesion on apolar substrates such as polyethylene and polypropylene. BGVV and FDA compliance (indirect food contact).

Initial Tack	Medium
Final Adhesion	High
Min. App. Temp	-5°C
Temp Range	-40°C to +120°C
UV Resistance	Excellent

Liner:

A supercalendered siliconised white glassine paper, with high mechanical resistance to tearing. Colour is white.

Thickness	57 micron $\pm 10\%$
Basic Weight	65 gsm $\pm 10\%$

Shelf Life:

2 years when stored at 22°C $\pm 2^\circ\text{C}$ and 50 $\pm 5\%$ RH.

The above specification is based on information obtained from the original manufacturer and is offered in good faith in accordance with the company's conditions to determine fitness for use. No guarantee is offered or implied. It is the ultimate user's responsibility to fully test the material and determine its suitability for the application intended. Measurements and test results are nominal. In accordance with a policy of continuous product improvement the manufacturer reserves the right to amend the specification without notice.